



CLASS	NOMINAL LENGTH					
	L ≤ 10	10 < L ≤ 30	30 < L ≤ 100	100 < L ≤ 300	300 < L ≤ 1000	1000 < L ≤ 3000
H	±0.02	±0.05	±0.1	±0.2	±0.3	±0.4
K	±0.05	±0.1	±0.2	±0.4	±0.6	±0.8

CLASS	NOMINAL LENGTH ON SHORTER SIDE			
	L ≤ 100	100 < L ≤ 300	300 < L ≤ 1000	1000 < L ≤ 3000
H	±0.2	±0.3	±0.4	±0.5
K	±0.4	±0.6	±0.8	±1.0

CLASS	STANDARD DIMENSION RANGE			
	L < 0.2	0.2 ≤ L ≤ 6	6 < L ≤ 30	30 < L ≤ 400
f	±0.1	±0.2	±0.5	±1.0
m	±0.1	±0.2	±0.5	±1.0

CLASS	STANDARD DIMENSION RANGE			
	L < 0.2	0.2 ≤ L ≤ 6	6 < L ≤ 30	30 < L ≤ 400
f	±0.1	±0.2	±0.5	±1.0
m	±0.1	±0.2	±0.5	±1.0

CLASS	STANDARD DIMENSION RANGE			
	L < 0.2	0.2 ≤ L ≤ 6	6 < L ≤ 30	30 < L ≤ 400
f	±0.1	±0.2	±0.5	±1.0
m	±0.1	±0.2	±0.5	±1.0

CLASS	STANDARD DIMENSION RANGE			
	L < 0.2	0.2 ≤ L ≤ 6	6 < L ≤ 30	30 < L ≤ 400
f	±0.1	±0.2	±0.5	±1.0
m	±0.1	±0.2	±0.5	±1.0

CLASS	STANDARD DIMENSION RANGE			
	L < 0.2	0.2 ≤ L ≤ 6	6 < L ≤ 30	30 < L ≤ 400
f	±0.1	±0.2	±0.5	±1.0
m	±0.1	±0.2	±0.5	±1.0

CLASS	STANDARD DIMENSION RANGE			
	L < 0.2	0.2 ≤ L ≤ 6	6 < L ≤ 30	30 < L ≤ 400
f	±0.1	±0.2	±0.5	±1.0
m	±0.1	±0.2	±0.5	±1.0

CLASS	STANDARD DIMENSION RANGE			
	L < 0.2	0.2 ≤ L ≤ 6	6 < L ≤ 30	30 < L ≤ 400
f	±0.1	±0.2	±0.5	±1.0
m	±0.1	±0.2	±0.5	±1.0

CLASS	STANDARD DIMENSION RANGE			
	L < 0.2	0.2 ≤ L ≤ 6	6 < L ≤ 30	30 < L ≤ 400
f	±0.1	±0.2	±0.5	±1.0
m	±0.1	±0.2	±0.5	±1.0

CLASS	STANDARD DIMENSION RANGE			
	L < 0.2	0.2 ≤ L ≤ 6	6 < L ≤ 30	30 < L ≤ 400
f	±0.1	±0.2	±0.5	±1.0
m	±0.1	±0.2	±0.5	±1.0

CLASS	STANDARD DIMENSION RANGE			
	L < 0.2	0.2 ≤ L ≤ 6	6 < L ≤ 30	30 < L ≤ 400
f	±0.1	±0.2	±0.5	±1.0
m	±0.1	±0.2	±0.5	±1.0

FOCAL LENGTH / 焦点距離 : 16mm
 MAX.APERTURE RATION / 最大口径比 : 1:2.5

FINISH	BLACK ANODIZING	UNIT:mm	
SURFACE		MODEL NAME	
MATERIAL	ALUMINUM ALLOY	PART NAME	OUTLINE DRAWING
CHAMFER		DRAWING NO.	A24570A0100101A-001
TOLERANCE CLASS		SHEET	1/1
SCALE	1:1		

MARK	A-001	2022.Nov.25	NEW		
DESIGNED	Y.Yokoi	DRAWN	Y.Yokoi	CHECKED	APPROVED
				モリテックス	モリテックス
				'22.12.02	'22.12.05
				岡	茅野