



焦点距離 : 74.5mm  
 光学倍率 : 0.8 ~ 1.0倍  
 Fno : 3.8 ~ 16

CLASS	NOMINAL LENGTH						CLASS	NOMINAL LENGTH ON SHORTER SIDE			
	L ≤ 10	10 < L ≤ 30	30 < L ≤ 100	100 < L ≤ 300	300 < L ≤ 1000	1000 < L ≤ 3000		L ≤ 100	100 < L ≤ 300	300 < L ≤ 1000	1000 < L ≤ 3000
H	±0.02	±0.05	±0.1	±0.2	±0.3	±0.4	H	±0.2	±0.3	±0.4	±0.5
K	±0.05	±0.1	±0.2	±0.4	±0.6	±0.8	K	±0.4	±0.6	±0.8	±1.0

STRAIGHTNESS & FLATNESS TOLERANCE	LENGTH OF SHORTER SIDE OF ANGLE	
	L ≤ 10	10 < L ≤ 400
PERPENDICULARITY TOLERANCE	NOMINAL LENGTH ON SHORTER SIDE	
	L ≤ 100	100 < L ≤ 3000
CLASS	ANGLE TOLERANCE	
	f	m
CLASS	STANDARD DIMENSION RANGE	
	L < 0.2	0.2 ≤ L ≤ 6
CLASS	CHAMFER TOLERANCE	
	f	m
CLASS	STANDARD DIMENSION RANGE	
	L < 0.2	0.2 ≤ L ≤ 6
CLASS	CHAMFER TOLERANCE	
	f	m
CLASS	STANDARD DIMENSION RANGE	
	L < 0.2	0.2 ≤ L ≤ 6
CLASS	CHAMFER TOLERANCE	
	f	m
CLASS	STANDARD DIMENSION RANGE	
	L < 0.2	0.2 ≤ L ≤ 6
CLASS	CHAMFER TOLERANCE	
	f	m

FINISH	BLACK ANODIZING	UNIT:mm	 Vision Creating Value
	SURFACE		
MATERIAL	ALLUMINUM ALLOY	MODEL NAME	ML-MC7538HR-0810
	CHAMFER	PART NAME	OUTLINE DRAWING
TOLERANCE CLASS	SCALE	DRAWING NO.	SHEET
	1:1		1/1
DESIGNED	DRAWN	CHECKED	APPROVED
Chino	Kevin	李研	侯仁毅
MARK	COM-REV	DATE(YMD)	CHANGE
A-001		2021.Aug.11	NEW
OLD DRAWING NO.	2		3