STRAIGHTNESS & FLATNESS TOLERANCE	CLASS	NOMINAL LENGTH					
		L ≤ 10	10 < L ≤ 30	30 < L ≤ 100	100 < L ≤ 300	300 < L ≤ 1000	1000 < L ≤ 3000
	H	±0.02	±0.05	±0.1	±0.2	±0.3	±0.4
	K	±0.05	±0.1	±0.2	±0.4	±0.6	±0.8

PERPENDICULARITY TOLERANCE	CLASS	NOMINAL LENGTH ON SHORTER SIDE			
		L ≤ 100	100 < L ≤ 300	300 < L ≤ 1000	1000 < L ≤ 3000
	H	±0.2	±0.3	±0.4	±0.5
	K	±0.4	±0.6	±0.8	±1.0

Absolute Max. Rating / 最大定格	DC24V
Total Power / 消費電力合計	1.2W
Mass / 質量	-

M12 Male Connector

Ref. Drawing	No	Assign	Wire Color
	1	+V	Red/Brown
	2	NC	
	3	-V	Black/Blue
	4	NC	



NO.	PART DESCRIPTION	MODEL NUMBER	QU.	NOTE
7				
6	CONNECTOR	M12Male	1	
5	CABLE LABEL		1	
4	CABLE		1	
3	DIFFUSER		1	
2	HOUSING		1	Aluminium Alloy / Glass Bead Blasted Black Anodizing
1	LED(RED)		-	

MARK	COM-REV	DATE(YMD)	CHANGE	SIGNATURE
x				
x				
x				
1 x5	A-002	2025.Apr.22	Add Cable Label , etc.	Okazaki
1	A-001	2022.Oct.13	NEW	-

DESIGNED	DRAWN	CHECKED	APPROVED
Yong Peng	Yong Peng	'25.04.23 土門	'25.04.24 達

FINISH: -
SURFACE: -
MATERIAL: -
CHAMFER: -
TOLERANCE CLASS: -
SCALE: 1:1

UNIT:mm

MORITEX
A Cognex Company

MODEL NAME: CV-FL-63X60R-M12

PART NAME: OUTLINE DRAWING

DRAWING NO.: A21819A0101001A-002

SHEET: 1/1

CLASS	LENGTH OF SHORTER SIDE OF ANGLE: L ≤ 10	10 < L ≤ 50	50 < L ≤ 120	120 < L ≤ 400	400 < L
f	±1°	±30' (±0.5°)	±20' (±0.333°)	±10' (±0.166°)	±5' (±0.083°)
m					

ANGLE TOLERANCE

ORIGINAL SHEET FORMAT SIZE : A3

CLASS	STANDARD DIMENSION RANGE: L < 0.2	0.2 ≤ L ≤ 0.5	0.5 < L ≤ 3	3 < L ≤ 6	6 < L
f	IN DRW.	±0.1	±0.2	±0.5	±1.0
m					

CHAMFER TOLERANCE

CLASS	STANDARD DIMENSION RANGE: L < 0.2	0.2 ≤ L ≤ 6	6 < L ≤ 30	30 < L ≤ 120	120 < L ≤ 400	400 < L ≤ 1000
f	IN DRW.	±0.05	±0.1	±0.15	±0.2	±0.3
m		±0.1	±0.2	±0.3	±0.5	±0.8

LENGTH TOLERANCE

OLD DRAWING NO.